


FEATURES

- Suction lance with valve and foot filter for PRIUS pumps from 250 to 1000 l/h
- Level probe sold separately
- Contact N.O.
- BNC connector
- Bottom filter
- Adjustable height
- 1 1/2 " fitting
- 1 1/2 " bottom filter
- PVC body
- Up to 2 suction outlets available

LASPM
1 OUTPUT



LASPM
2 OUTPUTS



SPECS

L	A	S	P	M	V	0	7	5	5	1	U	0	3	,	5	5	0	0	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

OUTPUTS (suction)	
1	1
2	2

LEVEL - CONTACT - CONNECTOR TYPE	
0	level - contact N.O. - BNC
4	without level



HOSE FITTINGS	
5	3/4" D.13
B	3/4" D.18
M	D.32

LENGTH cm	
075	75
108	108
122	122



O-RING	
V	FKM B
D	Ethylene Propylene

MEASURES

EFFECTIVE LENGTH	TANK VOLUME
75 cm	250 lt (mod. CNT PD 250)
108 cm	500 lt (mod. CNT PD 500)
122 CM	1000 lt (mod. CNT PD 1000)



LASPM 1		
A (mm)	B	C
750	100	60
1080		
1220		



LASPM 2		
A	B	C
750	100	60
1080		
1220		