IN-LINE PROBE HOLDERS
"PEA" - "PEB"

Data Sheet

FEATURES

- In-line and immersion probe-holders
- Easy assembling

SPECIFICATIONS

PEA in-line probe-holder

Electrodes	pH, ORP Ø 12
Max operating pressure	7 bar (3bar)
Max temperature	90°C (130°C)
Fittings	1/2"
Material	PVDF



PEB in-line probe-holder

Electrodes	pH, ORP Ø 12
Max operating pressure	7 bar (3bar)
Max temperature	90°C (130°C)
Fittings	3/4"
Material	PP

PEA/SN6 in-line probe-holder

Electrodes	pH, ORP, threading PG 13.5
Max operating pressure	7 bar
Max temperature	90°C
Fittings	1/2"
Material	PVDF



Via Donatori di Sangue, 1 - 02100 Rieti (Italy)
+39 074622841 | emecpumps.com

Specifications subject to change without notice | R2025

emec SIMPLE AS WATER

IQNET CERTIFIED MANAGEMENT SYSTEM
qualityaustria SYSTEM CERTIFIED
ISO 9001:2015 No.07728/0
ISO 14001:2015 No.00997/0
ISO 45001:2018 No.01121/0

IN-LINE PROBE HOLDERS
"PEA" - "PEB"

Data Sheet

PEA / PEB EXPLODED VIEW

EXEMPLE:
PEA / PEB INSTALLATION
ON EPH PROBE



Via Donatori di Sangue, 1 - 02100 Rieti (Italy)
+39 074622841 | emecpumps.com

Specifications subject to change without notice | R2025

emec
SIMPLE AS WATER

IQNET CERTIFIED MANAGEMENT SYSTEM
qualityaustria SYSTEM CERTIFIED
ISO 9001:2015 No.07728/0
ISO 14001:2015 No.00997/0
ISO 45001:2018 No.01121/0